






FLASHOVER PROTECTION IN ALL THE RIGHT PLACES

Australian firefighters work in the harshest environments, and need clothing and equipment that provide protection and comfort so they can focus on saving lives. Life Liners flash hoods are designed with Easy Seal™ face openings for fast donning of the hood while providing a tight seal on the SCBA mask.

The Life Liner PBI Flash Hood is constructed from a separate head piece and bib for a superior fit. The fabric is a unique combination of PBI® and Lenzing FR stitched together with 100% Nomex® thread. This combination results in a premium level of protection against heat, flame and flashover while remaining soft and lightweight for optimum user comfort. Life Liner flash hoods are third party certified and compliant with NFPA 1971.



CERTIFICATIONS	FABRIC	CODE	DESCRIPTION
NFPA 1971-2018 UL Certified meets or exceeds Cal/OSHA Stds. Title 8 Article 10.1 Sec. 340	20% PBI®/ 80% Lenzing FR	FHPFR9723ES	PBI® Flash Hood
DESIGN	LAYERS	 <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  STRUCTURAL FIREFIGHTING </div> <div style="text-align: center;">  NFPA 1971:2018 </div> </div> <div style="display: flex; justify-content: space-around; align-items: center; margin-top: 10px;"> <div style="text-align: center;">  FLASHOVER PROTECTION </div> <div style="text-align: center;">  2 LAYER CONSTRUCTION </div> </div>	
Head Design: separate head with sewn on back and front bib Back of head: ends at the nape of the neck for improved fit and comfort Bib Design Two piece design with 15cm front with 20cm back bib design	Head: 2 Layer Bib: 2 Layer Face Opening: Easy-Seal Face opening that goes on easy. Seals tight Sewn with 1.25cm elastic encapsulated in hood material Measures: 12.5cm - 14cm diameter (Relaxed) Fully Stretched Measurement: Exceeds 38cm		
WEIGHT	THREAD		
185gsm	100% Nomex®		
LABELS	CONSTRUCTION		
Each hood is labelled with an FR Label with all four label edges sewn to the hood, identifying material contents, UL certification, lot#, date of manufacture, and care instructions	Head Seams: All head and bib seams are sewn with a flat lock stitch Binding: 3.8cm binding sewn to hem through folder with a three thread cover stitch to create a 1.25cm finished bound hem		